Conventional Detector Mounting Base for 2-Wire Systems *YBO-R/6PA*



Features

- Integral remote indicator output
- Rugged design
- Dedicated cable screen terminal
- Quick connection via square cable clamps Accepts from 1 to 2.5 mm² cables
- Bayonet slot, low insertion force for detectors

Description

Model YBO-R/6PA is a Conventional Detector Mounting Base for 2-Wire S systems where detectors and sounders are on same zone cables*.

Specification	
Ordering Code	YBO-R/6PA
Operating Voltage	15 – 30 V dc
Operating Temperature Range	-10 °C to + 50 °C
Storage Temperature Range	-30 °C to + 60 °C
Maximum Humidity	95%RH - Non Condensing (at 40 °C)
Colour / Material	Ivory White /ABS
Weight (g) / Diameter (mm) / Height (mm)	80 / 100 / 13
Fixing Centres (mm)	48 ~ 74
Maximum Wire Thickness	2.5 mm ² Cables

*Control Panel compatibility required

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.